



Snagit® 12

COM Documentation

Version 12.0.0

May 2014

© 2014 TechSmith Corporation

All rights reserved

This manual, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. The content of this manual is furnished for informational use only, is subject to change without notice and should not be construed as a commitment by TechSmith Corporation. TechSmith Corporation assumes no responsibility or liability for any errors or inaccuracies that may appear in this manual.

Trademarks

All-in-One Capture, Camtasia, Camtasia Relay, Camtasia Studio, Coach's Eye, DubIt, EnSharpen, Enterprise Wide, Expressshow, Jing, Morae, Rich Recording Technology (RRT), Screencast.com, ScreenChomp, Show The World, SmartFocus, Snagit, TechSmith, TechSmith Fuse, TSCC and UserVue are either registered marks or marks of TechSmith Corporation in the U.S. and/or other countries. This list is not a comprehensive list of all TechSmith Corporation marks. The absence of a name/mark or logo in this notice does not constitute a waiver of any intellectual property rights that TechSmith Corporation has established in any of its product, feature or service names/marks or logos. All other marks are the property of their respective owners.

Table of Contents

Introduction to the Snagit COM Server	1
Installation Information	1
Getting Started	3
How It Works	3
Image Capture Code Tutorial	4
Interfaces	6
IAutoScrollOptions	7
IClipboardOptions	7
IDelayOptions	7
IExtendedWindowOptions	8
IFTPOptions	9
IImageAnnotation	10
IImageBorder	11
IImageCaptionOptions	12
IImageCapture	13
IImageCapture2	17
IImageCaptureResults	21
IImageColorConversion	21
IImageColorEffects	22
IImageColorSubstitution	23
IImageFile	24
IImageFilters	25
IImageResolution	26
IImageScale	26
IImageTrim	27
IImageWatermark	28
IMailOptions	30
IMenuOptions	31
IMP4Format	31
IPrinterOptions	31

IPrinterPageLayoutOptions	33
IRegionOptions	33
ISelectedArea	34
ITextAnnotation	35
ITextFont	36
ITWAINOptions	36
IVideoCapture	37
IVideoFile	40
IWindowOptions	41
Enumerations	43
snagAutoScrollMethod	43
snagAutoScrollStartingPosition	44
snagCaptionTextStyle	44
snagCaptureState	44
snagColorConversionMethod	45
snagColorSubMethod	45
snagCompassDirection	45
snagError	46
snagHotspotType	46
snagImageColorDepth	47
snagImageFileSubType	47
snagImageFileType	49
snagImageInput	50
snagImageOutput	50
snagImageScaleBy	51
snagImageScaleMethod	51
snagNotificationType	51
snagOutputFileNamingMethod	52
snagPlacement	52
snagPrintScale	53
snagRecorderError	53
snagRecorderState	54

snagRegionSelectionMethod	55
snagTimeDateOrder	55
snagTrimMethod	55
snagVideoFileType	55
snagVideoInput	56
snagVideoOutput	56
snagWindowSelectionMethod	56
Events	57
Methods	57
_IRecorderEvents Methods	58
Data Types	59
Boolean	59
Long	59
String	59
Interface	59
Colors	59
Code Samples	60
C++/ATL	60
C#	61
Visual Basic .NET	62
Visual Basic Script	63
Visual Basic	64

Introduction to the Snagit COM Server

Using Snagit's COM Server, you can easily incorporate Snagit's screen capture functionality into your organization's proprietary applications. The COM Server lets you customize capture instructions for Snagit, automate the capture process, and programmatically control Snagit's entire array of image and capture features from within your own application.

You can access Snagit's capture functionality from any programming language that supports COM, including the following:

- ▶ Visual Basic
- ▶ VBScript
- ▶ Visual C/C++
- ▶ Visual Studio .NET C#
- ▶ Delphi
- ▶ C++Builder

This Snagit COM Server User Guide assumes you are familiar with COM programming. If you need more information about COM, please consult your development environment's documentation.

Installation Information

The Snagit COM Server is built into Snagit. Download and install Snagit. This automatically registers the Snagit COM Server and makes it available to other applications.

The Snagit COM Server is implemented as an out-of-process COM Server. The Snagit setup program registers the Snagit COM Server after you install Snagit. If you need to manually register the COM Server, use a command prompt and type the following from the Snagit program folder:

```
Snagit32.exe /register
```

Application Deployment and Licensing

Each desktop using the Snagit COM Server must have Snagit installed. Any commercially distributed software application using the Snagit COM Server must comply with the restrictions found in the Snagit Software License Agreement found in the license.txt file in the Snagit application folder.

If you are using the Snagit evaluation version, the COM Server is fully functional during the 30-day evaluation period. Once the 30-day period has expired, invoking the capture method fails, and the COM Server gives a **serrSnagitExpired** error, and **LastError** is set to **serr-SnagitExpired**. All programs using the Snagit COM Server should check the **LastError** property or subscribe to the events from the capture interfaces, so that this error case is handled correctly.

System Requirements

An application using the Snagit COM Server must meet the following system requirements:

- ▶ Windows 7, or Windows 8 and newer (32-bit and 64-bit) installed and configured on your system
- ▶ Internet Explorer 8.0 or later required
- ▶ .NET 4.0 Full or later
- ▶ 2.4 GHz single core processor (2.4 GHz dual core required for video)
- ▶ 1 GB of RAM (2 GB required for video)
- ▶ 125 MB of free hard disk space
- ▶ Video capture on Windows 7 requires Windows 7 supported video and audio hardware
- ▶ Video capture on Windows 7 N requires the Media Feature Pack for Windows 7 N
- ▶ Snagit add-in for Microsoft Internet Explorer works with Internet Explorer 6.0 or later
- ▶ Snagit requires Active Accessibility 2.0 to capture links from webpages
- ▶ Snagit Stamps requires Snagit 6.3 or later

Getting Started

The Snagit COM Server should be accessible from any language that supports COM. Only basic data types are used, see [Data Types](#) for more information.

The Snagit COM Server is not an automation server. None of the changes made through the COM Server are saved in the Snagit application or the registry. You can use the COM Server from multiple clients, so check return values on calls to methods in case a conflict has occurred.

How It Works

All the interfaces, properties, and methods described in this user guide are accessible from any COM enabled language. All the interfaces, properties, and methods described in this user guide are accessible from any COM enabled language.

Interfaces	These define the properties, methods, and events for a given COM object.
Properties	Values stored in an interface that may be set or retrieved. Some properties are read only; all interfaces are read only.
Methods	Functions in interfaces that interact with the COM server.
Events	Events may be sent from the COM server to the client program. The client program must “subscribe” to the event interface to receive the events. This is a language dependent option, and not all programming languages can receive events.
Enumerations	There are many enumerations used in the Snagit COM server. These are described individually in the Enumerations section.

To access the COM object’s functionality, you must first create an instance of the object in your client program. See the tutorial for an example using Visual Basic 6.

► C++ MFC and ATL Users

The easiest way to make use of the COM server is using the Microsoft Visual C++ #import statement on the Snagit.tlb file present in the Snagit install directory. This creates smart-pointer wrapper classes for the COM server.

► Visual Basic 6 Users

A reference to the SNAGIT 1.0 Type Lib should be added in the *References* dialog accessed from the **Project > References** menu item.

► VB.NET and C# Users

Choose **Project > Add Reference** to add a reference to the SNAGIT 1.0 Type Lib. Note that the entry is on the COM tab page.

Image Capture Code Tutorial

This section gives you step-by-step instructions on the basic methods and properties you need to create an image capture. The source code fragments are given using Microsoft's Visual Basic programming language.

See the section on Visual Basic in Language Specific Samples for the complete source code showing how to use the COM object. View additional samples in the following programming languages:

- ▶ C++/ATL
- ▶ C#
- ▶ VB.NET
- ▶ VBScript

Step 1 – Creating the Capture Object

Create the capture object.

```
Dim ImageCapture1 As SNAGITLib.ImageCapture  
  
Set ImageCapture1 = CreateObject("Snagit.ImageCapture.1")
```

Step 2 – Setting the Capture Properties

Configure various capture object properties. All object properties use default values if the property is not specified. Configure different properties based on what you want to do with the capture object.

```
// Configure to capture the a window and save to the clipboard  
  
ImageCapture1.Input = siiWindow  
  
ImageCapture1.Output = sioClipboard
```

If you do not know the current capture setting, you can retrieve these values.

```
Dim bUsePreview  
  
bUsePreview = ImageCapture1.EnablePreviewWindow  
  
Dim CaptureCursor CaptureCursor = ImageCapture1.IncludeCursor
```

Step 3 – Starting the Capture

Once the capture object is configured correctly, start the capture session.

```
ImageCapture1.Capture
```

The Capture call is asynchronous. The capture object may still be completing the operation after the function returns.

Step 4 – Getting Capture Information

During or after a capture, you may want to monitor the state of the capture.

```
Dim capState As snagCaptureState  
capState = ImageCapture1.CaptureState  
  
Dim capDone  
capDone = ImageCapture1.IsCaptureDone
```

The capture state information resets when a new capture is started.

Specific interfaces send event callbacks to which a client can subscribe. This allows the client program to update without polling.

Interfaces

Interfaces define the methods and properties of the COM object.

When available, methods are listed before properties on interface pages.

Properties can be write or read only. Any property that is used to access another interface is read only.

The following interfaces are available:

- ▶ [**IAutoScrollOptions**](#)
- ▶ [**IClipboardOptions**](#)
- ▶ [**IDelayOptions**](#)
- ▶ [**IExtendedWindowOptions**](#)
- ▶ [**IFTPOptions**](#)
- ▶ [**ImageAnnotation**](#)
- ▶ [**ImageBorder**](#)
- ▶ [**ImageCaptionOptions**](#)
- ▶ [**ImageCapture**](#)
- ▶ [**ImageCapture2**](#)
- ▶ [**ImageCaptureResults**](#)
- ▶ [**ImageColorConversion**](#)
- ▶ [**ImageColorEffects**](#)
- ▶ [**ImageColorSubstitution**](#)
- ▶ [**ImageFile**](#)
- ▶ [**ImageFilters**](#)
- ▶ [**ImageResolution**](#)
- ▶ [**ImageScale**](#)
- ▶ [**ImageTrim**](#)
- ▶ [**ImageWatermark**](#)
- ▶ [**IMailOptions**](#)
- ▶ [**IMenuOptions**](#)
- ▶ [**IMP4Format**](#)
- ▶ [**IPrinterOptions**](#)
- ▶ [**IPrinterPageLayoutOptions**](#)
- ▶ [**IRegionOptions**](#)
- ▶ [**ISelectedArea**](#)
- ▶ [**ITextAnnotation**](#)
- ▶ [**ITextFont**](#)
- ▶ [**ITWAINOptions**](#)
- ▶ [**IVideoCapture**](#)
- ▶ [**IVideoFile**](#)
- ▶ [**IVideoFormat**](#)
- ▶ [**IWindowOptions**](#)

IAutoScrollOptions

The **IAutoScrollOptions** interface contains the settings for scrolling captures. These settings are only valid when the input of the capture object is set to **siiWindow** or **siiRegion** on an image capture object and **stoWindow** or **stoRegion** on a text capture object.

Properties

Property (type)	Default	Read / Write	Notes
AutoScrollMethod (sna-gAutoScrollMethod)	sasmNone	Write	Sets the type of automatic scrolling for the next capture. See sna-gAutoScrollMethod for information on possible options.
ForegroundScrollingWindow (Boolean)	True	Write	If enabled, the next capture performed brings the window to be scrolled to the foreground and displays the window while scrolling.
Delay (long)	0	Write	The time, in seconds, to wait between foregrounding the window and capturing. Valid values are 0 to 300000.
StartingPosition (sna-gAutoScrollStartingPosition)	sassp-TopLeft	Write	The position from which the window is scrolled. For more information, see sna-gAutoScrollStartingPosition .

IClipboardOptions

The **IClipboardOptions** interface is used to set the options related to Clipboard capture input.

Properties

Property (type)	Default	Read / Write	Notes
WidthInPixels (long)	640	Write	Controls the width (in pixels) of Clipboard capture images. Set this value to zero to use the Windows desktop width and height for image dimensions.

IDelayOptions

The **IDelayOptions** interface specifies the number of seconds to wait before taking a capture.

Properties

Property (type)	Default	Read / Write	Notes
EnableDelayedCapture (Boolean)	False	Write	If set to true, the Snagit COM server waits for the period of time specified in the DelaySeconds property before performing the capture.
DelaySeconds (long)	10	Write	Specifies the number of seconds to delay before performing a capture. Ignored if EnableDelayedCapture is set to false.
EnableCountdownWindow (Boolean)	True	Write	If set to true, a countdown is displayed showing the number of seconds left before the capture occurs. Ignored if EnableDelayedCapture is set to false.

IExtendedWindowOptions

The **IExtendedWindowOptions** interface contains all the settings for an extended window capture. Extended window capture allows you to resize a window to any width/height before capturing (potentially bigger than the screen). The window is restored to its original width/height after capture is completed. You can also use this option to capture a window partially off the screen.

Only valid when capturing an image object using the **siiExtendedWindow** input.

Properties

Property (type)	Default	Read / Write	Notes
EnablePreview (Boolean)	True	Write	If true, the user sets the height and width for the extended window capture. Ignored if UseSpecifiedCaptureSize is false.
Height (long)	600	Write	The height to size the window before taking the capture. Must be a positive integer.
UseSpecifiedCaptureSize (Boolean)	True	Write	
Width (long)	800	Write	The width to size the window before taking the capture. Must be a positive integer.

IFTPOptions

The **IFTPOptions** interface is used when the output is set to **sioFTP** or **stoFTP**. The image capture is sent to an FTP server. At a minimum, the server and filename must be set in order to use FTP output.

Properties

Property (type)	Default	Read / Write	Notes
EnableProgressDialog (Boolean)	False	Write	When true, displays a dialog that detailing the status of the current transfer.
Filename (string)	"" (empty string)	Write	File name to use if UseAutomaticFileNaming is false, or the prefix of the file name if UseAutomaticFileNaming is true.
Password (string)	"" (empty string)	Write	Password on the FTP server, if it requires authentication. Use with ServerRequiresAuthentication .
Port (long)	21	Write	The port of the FTP server to upload to.
ProxyServer (string)	"" (empty string)	Write	Specifies both the proxy server name and the port in the format "server:port". Only used if UseProxyServer is true.
RemotePath (string)	"" (empty string)	Write	Path to a directory on the remote server to put the output file. This can be relative or absolute, but must exist.
SequenceLimit (long)	0	Write	Limits the number of auto-named files stored on the FTP server (oldest file is deleted). Use 0 for no limit.
Server (string)	"" (empty string)	Write	Location of the FTP server to upload to. This does not need the "ftp://" prefix.
ServerRequiresAuthentication (Boolean)	False	Write	Use with UserName and Password .
UseAutomaticFileNaming (Boolean)	False	Write	When true, the file is automatically named. Numbers are appended to the end of the file name, starting with 1. Files of separate types (extensions) have separate numbering.
UsePassiveFTP (Boolean)	False	Write	Enable or disable passive FTP mode.

Property (type)	Default	Read / Write	Notes
EnableProgressDialog (Boolean)	False	Write	When true, displays a dialog that detailing the status of the current transfer.
UseProxyServer (Boolean)	False	Write	Use when routing transfers through a proxy server.
UserName (string)	"" (empty string)	Write	User name on the FTP server, if it requires authentication. Use with Server-RequiresAuthentication .
UseTempFileReplace (Boolean)	True	Write	When true, the is uploaded under a temporary name and then renamed to the appropriate output file name.

IImageAnnotation

The **IImageAnnotation** interface allows for overlaying user or system captions on the captured image. The length of the string is limited by width of the image or by the width of the printed page. The text is truncated if it is too long.

Properties

Property (type)	Default	Read / Write	Notes
EnableCaption (Boolean)	False	Write	Enables the text caption.
PromptForCaption (Boolean)	False	Write	Prompts the user for caption text. Ignored if EnableCaption is set to false.
CaptionText (string)	"" (empty string)	Write	The text use in the caption.
IncludeComputerName (Boolean)	False	Write	Appends the name of the computer to the caption.
IncludeUserName (Boolean)	False	Write	Appends the name of the current user to the caption.
IncludeTimeDate (Boolean)	False	Write	Appends the time and/or date to the system caption.
TimeDateDisplayOrder (snagTimeDateOrder)	stdoTimeThenDate	Write	Defines if, and in what order, to display the time and date.
UseWindowsTimeFormat	True	Write	Use current Windows stand-

Property (type)	Default	Read / Write	Notes
(Boolean)			ard format for time.
UseWindowsDateFormat (Boolean)	True	Write	Use current Windows standard format for date.
CustomTimeFormat (string)	"" (empty string)	Write	Text representing the format of the time, such as "h:mm:ss tt".
CustomDateFormat (string)	"" (empty string)	Write	Text representing the format of the date, such as "M/d/yyyy".
PrintCaptionsAtPageBottom (Boolean)	True	Write	If true, the caption is not printed over the image, but instead added to the bottom.
CaptionOptions (IImageCaptionOptions)		Read	An interface containing settings for the text displayed as a caption.
SystemCaptionOptions (IImageCaptionOptions)		Read	An interface containing settings for the text displayed as a caption.

IImageBorder

The **IImageBorder** interface is a filter that creates a border around the edge of an image. This filter may increase the size of the original captured image.

Properties

Property (type)	Default	Read / Write	Notes
EnableBorder (Boolean)	False	Write	Enables the border filter.
FrameOutsideImage (Boolean)	True	Write	If true, draws the border outside the bounds of the captured image.
Use3DEffect (Boolean)	True	Write	Uses three colors to create a 3D effect.
TotalWidth (long)	8	Write	The total width of the border, in pixels.
ShadowWidth (long)	2	Write	The width, in pixels, of the shadow effect. Valid values are 0 to one half of the value of

Property (type)	Default	Read / Write	Notes
			TotalWidth.
MainColor (long)	RGB (192, 192, 192)	Write	The default border color. Any RGB color is a valid value. This is the only color used if Use3DEffect is false.
HighlightColor (long)	RGB (255, 255, 255)	Write	The highlight color of the 3D border effect. Any RGB color is a valid value. This color is used only if Use3DEffect is true.
ShadowColor (long)	RGB (128, 128, 128)	Write	The shadow color of the 3D border effect. Any RGB color is a valid value. This color is used only if Use3DEffect is true.

For more information on RGB color values, see [Colors](#).

IIImageCaptionOptions

The **IIImageCaptionOptions** interface contains the settings for the text that is added as a caption to image captures. Use [IIImageAnnotation](#) to turn add captions to image captures.

Properties

Property (type)	Default	Read / Write	Notes
BackgroundColor (long)	RGB (0, 0, 0)	Write	The background color of the rectangle on which the text is displayed. Any RGB color is a valid value. If UseTransparentBackground is true, this property is not used.
CaptionStyle (snag-CaptionTextStyle)	sctsNormal	Write	Text style for the caption.
Font (ISelectedArea)		Read	An interface that exposes the bounding box around the captured area.
OutlineColor (long)	RGB (255, 255, 255)	Write	The color of the outline that surrounds the text. Any RGB color is a valid value.

Property (type)	Default	Read / Write	Notes
Placement (snagPlacement)	spCenterTop	Write	Where the text is placed on the captured image.
ShadowColor (long)	RGB (192, 192, 192)	Write	The color of the drop shadow effect for the text. Any RGB color is a valid value.
TextColor (long)	RGB (0, 0, 0)	Write	The font color. Any RGB color is a valid value.
UseTransparentBackground (Boolean)	False	Write	Hides the rectangle on which the text is displayed.
UseWordWrap (Boolean)	True	Write	Wraps the text to a new line if the text is wider than the display area.

For more information on RGB color values, see [Colors](#).

IImageCapture

The **IImageCapture** interface is the base capture interface for image captures. All image capture actions and settings are contained within it.

If your users have Snagit version 8.1.0 or later, use the **IImageCapture2** interface for image captures.

Methods

Name	Action	Notes
Capture	Invokes an image capture	Moves the Snagit COM server into a busy state while the capture is performed. This is always non-blocking except when the output mode is set to sioFile with the Editor window disabled. In order to know when a capture finishes, subscribe to either the _ICaptureEvents or poll the IsCaptureDone property.

Properties

Property (type)	Default	Read/Write	Notes
AutoScrollOptions ()		Read-only	An interface containing the settings for scrolling captures.
BackgroundColor (Long)	RGB(255, 255, 255)	Write	Sets the background color to use outside the capture area for the next capture performed. Any RGB color value is valid (see Colors).
CaptureMultipleAreas (Boolean)	False	Write	Enables or disables multiple area selection for the next capture performed.
CaptureState (snag-CaptureState)	scsIdle	Read-only	Returns the current capture state set by the Snagit COM server. Instead of subscribing to the event interface, you can poll this property for the state of the Snagit COM server.
ClipboardOptions (IClipboardOptions)		Read-only	An interface to set options related to Clipboard capturing inputs.
DelayOptions (IDelayOptions)		Read-only	An interface that allows for a capture to be called after a specified number of seconds.
EnablePreviewWindow (Boolean)	False	Write	Enables or disables the Editor window for the next capture.
Filters (IImageFilters)		Read-only	A collection of interfaces for adjusting a captured image.
ForegroundPreview (Boolean)	True	Write	When enabled, this forces the Editor window into the foreground (gives it focus) after making a capture. Only valid if EnablePreviewWindow is set to true.
IncludeCursor (Boolean)	True	Write	Enables or disables the inclusion of the mouse cursor for the next capture performed.
Input (snagImageInput)	siiWindow	Write	Changes the input mode for

Property (type)	Default	Read/Write	Notes
AutoScrollOptions ()		Read-only	An interface containing the settings for scrolling captures.
			the next capture performed. The input mode determines where the Snagit COM server captures the bitmap from.
InputExtendedWindowOptions (IExtendedWindowOptions)		Read-only	An interface containing all settings for an Extended Window capture.
InputMenuOptions (IMenuOptions)		Read-only	An interface containing all settings for a Menu capture (input set to siiMenu).
InputRegionOptions (IRegionOptions)		Read-only	An interface containing all the settings for a Region capture (input set to siiRegion or stiRegion).
InputTWAINOptions (ITWAINOptions)		Read-only	An interface containing all the settings for a TWAIN capture (input mode set to siiTwain).
InputWindowOptions (IWindowOptions)		Read-only	An interface containing the settings for a Window capture (input set to siiWindow or stiWindow).
IsCaptureDone (Boolean)	False	Read-only	After a call to the Capture method has been made, this property tests to see if the capture has been completed. This property blocks and performs a polling to see when the capture state goes back to scsIdle .
LastCaptureSucceeded (Boolean)	True	Read-only	Returns true if the last capture attempt was successful. Returns false if the last capture attempt was unsuccessful.
LastError (snagError)	serrNone	Read-only	Holds the last error set in the Snagit COM server. If an application subscribes to the OnStateChange event of the _ICaptureEvents interface, this property can be read for the

Property (type)	Default	Read/Write	Notes
AutoScrollOptions ()		Read-only	An interface containing the settings for scrolling captures.
			error on a scsCaptureFailed state change. This property is reset to serrNone when a new call to the Capture method is made.
LastFileWritten (string)	"" (empty string)	Read-only	If the last capture used sioFile as the output, this property contains the whole path for the resulting image file.
NotificationType (snag-NotificationType)	sntNone	Write	Sets the messages the Snagit COM server displays. For more information on notifications see snag-NotificationType enumeration description.
Output (snagImageOutput)	sioFile	Write	Changes the output mode for the next capture performed. The output mode determines what the Snagit COM server does with the resulting bitmap from the capture.
OutputFTPOptions (IFTPOptions)		Read-only	An interface containing settings for sending the capture out to FTP (output set to sioFTP or stoFTP). At a minimum, server and filename must be set.
OutputImageFile (IImageFile)		Read-only	An interface for the configuration of an output image file.
OutputMailOptions (IMailOptions)		Read-only	An interface for setting email output information. Either all information is specified and the email is sent immediately, or the user is prompted for all information.
OutputPrinterOptions (IPrinterPageLayoutOptions)		Read-only	An interface used to specify the formatting of an output being sent to a printer (output set to sioPrinter or

Property (type)	Default	Read/Write	Notes
AutoScrollOptions ()		Read-only	An interface containing the settings for scrolling captures.
			stoPrinter).
UseMagnifierWindow (Boolean)	True	Write	When enabled, a magnifier window shows next to the capture crosshairs for precision when defining capture regions.

IIImageCapture2

The **IIImageCapture** interface is the base capture interface for image captures. All image capture actions and settings are contained within it.

IIImageCapture2 replaces **IIImageCapture** for users of versions 8.1.0 and later.

Methods

Name	Action	Notes
Capture	Invokes an image capture	<p>Moves the Snagit COM server into a busy state while the capture is performed.</p> <p>This is always non-blocking except when the output mode is set to sio-File with the Editor window disabled. In order to know when a capture finishes, subscribe to either _ICaptureEvents or poll the IsCaptureDone property.</p>

Properties

Property (type)	Default	Read/Write	Notes
AutoScrollOptions (IAutoScrollOptions)		Read-only	An interface containing the settings for scrolling captures.
BackgroundColor (long)	RGB(255, 255, 255)	Write	Sets the background color to use outside the capture area for the next capture performed. Any RGB color value is valid (see Colors).

Property (type)	Default	Read/Write	Notes
CaptureMultipleArea (Boolean)	False	Write	Enables or disables multiple area selection for the next capture performed.
CaptureResults (Image-CaptureResults)		Read-only	An interface that stores information about what happened during a capture.
CaptureState (snagCaptureState)	scsIdle	Read-only	Returns the current capture state set by the Snagit COM server. Instead of subscribing to the event interface, you can poll this property for the state of the Snagit COM server.
ClipboardOptions (IClipboardOptions)		Read-only	An interface to set options related to Clipboard capturing inputs.
DelayOptions (IDelayOptions)		Read-only	An interface that allows for a capture to be called after a specified number of seconds.
EnablePreviewWindow (Boolean)	False	Write	Enables or disables the Editor window for the next capture.
Filters (ImageFilters)		Read-only	A collection of interfaces for adjusting a captured image.
ForegroundPreviewWindow (Boolean)	True	Write	When enabled, this forces the Editor window into the foreground (gives it focus) after making a capture. Only valid if EnablePreviewWindow is set to true.
HotspotType (snagHotspotType)	shtNone	Write	Changes the type of hotspot captured. Hotspots are not compatible with all capture types.
IncludeCursor (Boolean)	True	Write	Enables or disables the inclusion of the mouse cursor for the next capture performed.

Property (type)	Default	Read/Write	Notes
Input (snagImageInput)	siiWindow	Write	Changes the input for the next capture. Input determines where the bitmap is captured from.
InputExtendedIWindowOptions (IExtendedWindowOptions)		Read-only	An interface containing all settings for an Extended Window capture.
InputMenuOptions (IMenuOptions)		Read-only	An interface containing all settings for a Menu capture (input set to siiMenu).
InputRegionOptions (IRegionOptions)		Read-only	An interface containing all the settings for a Region capture (input set to siiRegion or stiRegion).
InputTWAINOptions (ITWAINOptions)		Read-only	An interface containing all the settings for a TWAIN capture (input mode set to siiTwain).
InputWindowOptions (IWindowOptions)		Read-only	An interface containing the settings for a Window capture (input set to siiWindow or stiWindow).
IsCaptureDone (Boolean)	False	Read-only	After a call to the Capture method has been made, this property tests to see if the capture has been completed. This property blocks and performs a polling to see when the capture state goes back to scsIdle .
LastCaptureSucceeded (Boolean)	True	Read-only	Returns true if the last capture attempt was successful. Returns false if the last capture attempt was unsuccessful.
LastError (snagError)	serrNone	Read-only	Holds the last error set in the Snagit COM server. If an application subscribes to the OnStateChange event of the _ICaptureEvents interface, this property can be read for the error on a

Property (type)	Default	Read/Write	Notes
			scsCaptureFailed state change. This property is reset to serrNone when a new call to the Capture method is made.
LastFileWritten (string)	"" (empty string)	Read-only	If the last capture used sioFile as the output, this property contains the whole path for the resulting image file.
NotificationType (snag-NotificationType)	sntNone	Write	Sets the messages the Snagit COM server displays. For more information on notifications see the snag-NotificationType enumeration description.
Output (snagImageOutput)	sioFile	Write	Changes the output for the next capture. Output determines what happens to the captured bitmap.
OutputFTPOptions (IFTPOptions)		Read-only	An interface containing settings for sending the capture out to FTP (output set to sioFTP or stoFTP). At a minimum, server and file-name must be set.
OutputImageFile2 (IImageFile2)		Read-only	An interface for the configuration of an output image file.
OutputMailOptions (IMailOptions)		Read-only	An interface for setting email output information. Either all information is specified and the email is sent immediately, or the user is prompted for all information.
OutputPrinterPageLayoutOptions (IPrinterPageLayoutOptions)		Read-only	An interface used to specify the formatting of output going to a printer. Only used when sioPrinter or stoPrinter is selected as the output.

Property (type)	Default	Read/Write	Notes
OutputPrinterOptions (IPrinterOptions)		Read-only	An interface for use with printer output. If UseDefaultPrinter is set to true then other values set programmatically by SetData or by the user with the ShowSelectionDialog are ignored.
UseMagnifierWindow (Boolean)	True	Write	When enabled, a magnifier window shows next to the capture crosshairs for precision when defining capture regions.

IIImageCaptureResults

The **IIImageCaptureResults** interface contains information about what happened during a capture.

Properties

Property (type)	Default	Read/Write	Notes
LastFileWritten (string)	"" (empty string)	Read-only	The file path for the image file if sioFile was used as the output.
SelectedArea (ISelectedArea)		Read-only	An interface that exposes the bounding box around the captured area. For a freehand region, this is the bounding box around the total area (e.g. the left-most or rightmost point of the selection).

IIImageColorConversion

The **IIImageColorConversion** interface sets an image's color resolution during capture.

Properties

Property (type)	Default	Read / Write	Notes
ConversionMethod (snag-ColorConversionMethod)	sccmNone	Write	By default, no color conversion occurs. If set to sccmCustom , the ColorDepth and dither settings are used. If set to sccmMonochrome , the

Property (type)	Default	Read / Write	Notes
			MonochromeThreshold is used.
MonochromeThreshold (long)	50	Write	A percentage value that determines the quantity of black and white that shows in the output image. Valid values are from 0 -100.

IImageColorEffects

The **IImageColorEffects** interface is a collection of filters that modify the colors of a captured image. Note that these ranges are different than those presented in the Snagit program.

Properties

Property (type)	Default	Read / Write	Notes
Brightness (long)	0	Write	Changes the intensity (brightness) of the image. Valid values are -1000 to 1000.
Contrast (long)	0	Write	Changes the contrast between light and dark portion of the image. Valid values are -1000 to 1000.
Hue (long)	0	Write	Changes the hue of colors in the image (similar to rotating a color wheel to select a different mixture of colors). Valid values are -360 to 360.
Saturation (long)	0	Write	Changes the saturation of colors in the image. Saturation is the quantity of a color in a pixel, from gray at the lowest saturation to rich color in the highest. Valid values are -1000 to 1000.
Gamma (long)	100	Write	Adjusts the intensity of colors in an image by changing the gamma constant used to map the intensity values. Gamma correction changes brightness using a logarithmic scale for visual perception; gamma is a constant used to calculate the progression. Valid values are 1 to 499.

IImageColorSubstitution

The **IImageColorSubstitution** interface allows colors in the captured image to be replaced. Multiple rules for color substitution can be added with the AddColorSub method.

Call **ClearColorSub** between captures to clear the current list of color substitutions.

Methods

Method	Action	Parameters	Notes
AddColorSub (long, OrigColor, long NewColor, long Accuracy, Boolean SwapColors)	Adds a color substitution to the list.	<p>[in] OrigColor (long): The color to be replaced.</p> <p>[in] NewColor (long): The color to replace the original color.</p> <p>[in] Accuracy (long): How close the color should be to the color being replaced.</p> <p>[in] SwapColors (Boolean): If true, colors are swapped instead of replaced.</p>	Colors are selected using RGB values.
ClearColorSub ()	Clears the current list of color substitutions.		
ShowColorSubDialog (long IParentHandle, Boolean dialogAccepted)	Immediately shows the color substitution dialog.	<p>[in] IParentHandle (long): Handle to window (hwnd) in 32-bit integer format. If the handle is not available, set to 0.</p> <p>[out] dialogAccepted (Boolean): True if the user selects OK to select a new color substitution. False if the user selects Cancel.</p>	

Properties

Property (type)	Default	Read / Write	Notes
ColorSubMethod (snag-ColorSubMethod)	sccsmNone	Write	Used to substitute colors for other colors.

For more information on RGB colors, see [Colors](#).

IImageFile

The **IImageFile** interface allows for the configuration of an output image file. Always call **LoadImageDefaults** after changing the **FileType** property.

Methods

Method	Action	Parameters
LoadImageDefaults (snag-ImageFileType , newFileType)	Sets the file type and loads the default attributes for that type (sub-type, quality, etc).	[in] newFileType (snag-ImageFileType): The file type to load default settings for.
ShowFileSettingDialog (long IParentHandle, snag-ImageFileType , newFileType, Boolean dialogAccepted)	Shows the dialog for a given file type and sets the file type if the user accepts the dialog.	[in] IParentHandle (long): Handle to windows (hwnd) in 32-bit integer format. If handle is not available, set value to 0. [out] dialogAccepted (Boolean): True if the user clicked OK to set new file type settings. False if the user clicked Cancel.

Properties

Property (type)	Default	Read / Write	Notes
AutoFilePrefix (string)	"SNAG-"	Write	When the FileNamingMethod is set to sofnmAuto , this string is the prefix used to automatically name files.
AutoNumPrefixDigits (long)	4	Write	When FileNamingMethod is set to sofnmAuto , this property specifies the number of digits to include in the automatically named output file.
ColorDepth (snag-ImageColorDepth)	sicdAuto	Write	Number of bits used for color encoding.
Directory (string)	"" (empty string)	Write	Sets the directory for the output file. If the FileNamingMethod is not set to sofnmPrompt , the

Property (type)	Default	Read / Write	Notes
			Snagit COM server fails if this property is not set.
Filename (string)	"SNAGIT"	Write	Specifies the output filename to use. This is only used if FileNamingMethod is set to sofnmFixed .
FileNamingMethod (snag-OutputFileNamingMethod)	sofnmPrompt	Write	Method for naming the output file.
FileType (snagImageFileType)	siftPNG	Write	The format of the output file. Use LoadImageDefaults to avoid unexpected results.
FileSubType (snag-ImageFileSubType)	-indeterminate-	Write	Further specifies the type of image file to save. Do not assume a default subtype; instead choose a compatible subtype, call LoadImageDefaults , or use the ShowFileSettingDialog function.
ProgressiveOption (long)	0 - 12	Write	Sets the number of scans for a progressively encoded image. A value of 0 means no progressive scan. This property is only valid if the FileType is set to siftJPEG .
Quality (long)	25	Write	Sets the quality of the compression on the image file. This property is only valid if the FileType property is set to siftJPEG . Valid values are 1 - 100.

IImageFilters

The **IImageFilters** interface is a collection of interfaces for adjusted captured images. Most filters can be used in conjunction if all choices are compatible.

Properties

Property (type)	Notes
Annotation (IImageAnnotation)	An interface for adding annotations to image captures.
Border (IImageBorder)	An interface for adding borders to image captures.
ColorConversion (IImageColorConversion)	An interface to convert colors in image captures.
ColorEffects (IImageColorEffects)	An interface for adding color effects to image captures.
ColorSubstitution (IImageColorSubstitution)	An interface for substituting colors in image captures.
Resolution (IImageResolution)	An interface for changing the resolution of image captures.
Scale (IImageScale)	An interface for resizing image captures.
Trim (IImageTrim)	An interface for trimming image captures.
Watermark (IImageWatermark)	An interface to add a watermark to image captures.

IImageResolution

The **IImageResolution** interface sets the number of dots per inch (DPI) of the image. These settings have no effect on how the Snagit COM server displays or prints the image.

Properties

Property (type)	Default	Read / Write	Notes
Resolution (long)	96	Write	If UseAutoResolution is false, sets the DPI resolution of the image.
UseAutoResolution (Boolean)	True	Write	If true, the Snagit COM server chooses the image resolution. If false, the value specified by Resolution is used.

IImageScale

The **IImageScale** interface resizes a captured image.

Rounded, or even proportioned, percentage settings scale faster than irregular ones. If you use a factor that is not proportional (58%, for example), enable **UseSmoothScaling** to improve the image's appearance.

Properties

Property (type)	Default	Read / Write	Notes
Factor (long)	0	Write	Percentage of the original width and height.
FactorHeight (long)	100	Write	Percentage of the original height.
FactorWidth (long)	100	Write	Percentage of the original width.
Height (long)	200	Write	Height, in pixels.
KeepAspectRatio (Boolean)	True	Write	Keeps the image aspect ratio fixed while changing the width or height.
ScaleBy (snag-ImageScaleBy)	sisbFactor	Write	
ScaleMethod (snag-ImageScaleMethod)	sismNone	Write	
UseSmoothScaling (Boolean)	True	Write	This applies a "smoothing" effect images, removing the appearance of jagged edges.
Width (long)	320	Write	Width, in pixels.

IImageTrim

The **IImageTrim** interface removes pixels from the edges of an image. If the **TrimMethod** is set to **stmAuto**, none of the other values in this interface are used.

Properties

Property (type)	Default	Read / Write	Notes
Bottom (long)	0	Write	The number of pixels to trim from the bottom of the image. Only valid if TrimMethod is set to stmManual .
Left (long)	0	Write	The number of pixels to trim from the left of the image. Only valid if TrimMethod is set to stmManual .

Property (type)	Default	Read / Write	Notes
Right (long)	0	Write	The number of pixels to trim from the right of the image. Only valid if TrimMethod is set to stmManual .
Top (long)	0	Write	The number of pixels to trim from the top of the image. Only valid if TrimMethod is set to stmManual .
TrimMethod (snag-TrimMethod)	stmNone	Write	Determines the method for how pixels are trimmed from an image.

IImageWatermark

The **IImageWatermark** interface is used to create a watermark on a captured image.

Properties

Property (type)	Default	Read / Write	Notes
EmbossDepth (long)	500	Write	Sets the depth of the emboss effect. Higher values created a deeper shadow effect. Valid values are 1-1000.
EmbossDirection ()	scdNorth	Write	Sets the direction of the appearance of the emboss. Ignored if UseEmboss is false.
ImageFilename (string)	"" (empty string)	Write	The filename of the image to be used for the watermark.
IncludeWatermark (Boolean)	False	Write	If true, a watermark is added in a fixed location to the image.
KeepAspectRatio (Boolean)	True	Write	If true, scaling performed on the watermark image retains the ratio between the width and height of the watermark source image file.
OffsetHorizontal (long)	10	Write	The amount the watermark is offset

Property (type)	Default	Read / Write	Notes
EmbossDepth (long)	500	Write	Sets the depth of the emboss effect. Higher values created a deeper shadow effect. Valid values are 1-1000.
EmbossDirection ()	scdNorth	Write	Sets the direction of the appearance of the emboss. Ignored if UseEmboss is false.
			horizontally, by a percentage of overall image size, from the placement set in the Position property, Valid values are 1 - 100.
OffsetVertical (long)	10	Write	The amount the watermark is offset vertically, by a percentage of overall image size, from the placement set in the Position property, Valid values are 1 - 100.
Position (snag-Placement)	spCenterBottom	Write	Sets the position of the watermark in the output image.
Scale (long)	15	Write	The level of scaling (by percentage) done to the watermark image before is added to the capture. Valid values are 1 - 100. In VB6, the "Scale" property is a reserved keyword. Use "ScaleSize" instead. (For Snagit version 8.1.0 or later.)
TransparentColor (long)	RGB (128, 128, 128)	Write	Any color in the watermark image matching the RGB value specified is not drawn over the captured image. This property is ignored unless UseTransparentColor is set to true.
UseEmboss (Boolean)	False	Write	If true, the watermark image is embossed on the capture.
UseOverlay (Boolean)	False	Write	If true, the watermark is placed on top of the image.

Property (type)	Default	Read / Write	Notes
EmbossDepth (long)	500	Write	Sets the depth of the emboss effect. Higher values created a deeper shadow effect. Valid values are 1-1000.
EmbossDirection ()	scdNorth	Write	Sets the direction of the appearance of the emboss. Ignored if UseEmboss is false.
UseSmoothScaling (Boolean)	True	Write	If true, the watermark image is smoothed using interpolation.
UseTransparentColor (Boolean)	False	Write	If true, any colors in the watermark image that are the same as the color in the TransparentColor property become transparent in the output image.

IMailOptions

The **IMailOptions** interface sets email output related items. Either all information must be specified and the email is sent immediately, or the user is prompted for all information.

Properties

Property (type)	Default	Read / Write	Notes
Address (string)	"" (empty string)	Write	The email recipient's email address.
MessageText (string)	"" (empty string)	Write	The body text of the email.
Name (string)	"" (empty string)	Write	The email sender's name.
PromptForSettings (Boolean)	False	Write	If false, name, address, subject, and text must be specified programmatically. If true, the user's mail client is shown and the information must be provided by the user. When true, set-

Property (type)	Default	Read / Write	Notes
			ting other values has no effect.
Subject (string)	"" (empty string)	Write	The subject line of the email.

IMenuOptions

The **IMenuOptions** interface contains all the settings for a menu capture (input set to **siiMenu**).

Properties

Property (type)	Default	Read / Write	Notes
CaptureCascaded (Boolean)	False	Write	When false, only the current menu is included in the capture. When true, the current menu and all parent menus are included in the capture.
IncludeBar (Boolean)	False	Write	Enable or disable inclusion of the menu bar in the capture.

IMP4Format

The IMP4Format is the default video format.

Property (type)	Default	Read / Write	Notes
VideoFileType (snag-VideoFileType)	svftMP4	Read-only	Returns current format.
DisableMOOVAAtomOptimization (Boolean)	FALSE	Write	Enables/disables the re-ordering of the MP4 atoms to optimize the file for streaming from the internet.

IPrinterOptions

The **IPrinterOptions** interface is used with printer output. If **UseDefault:Printer** is set to true then any other values set programmatically by **SetData** or by the user with **ShowSelectionDialog** are ignored.

Methods

Method	Action	Parameters	Notes
GetData (string PrinterName, string DriverName, string Port)	Retrieves data about the selected printer.	[out] PrinterName (string): The name of the selected printer. [out] DriverName (string): The name of the driver installed for the printer. [out] Port (string): The port of the selected printer.	
SetData (string PrinterName, string DriverName, string Port)	Sets the printer for the Snagit capture object to use.	[in] PrinterName (string): The name of the printer to use. [in] DriverName (string): The name of the printer driver to use. [in] Port (string): The port of the selected printer.	If UseDefault:Printer is true, data set with this call is over-written.
ShowSelectionDialog (long IParentHandle, Boolean dialogAccepted)	Displays a printer selection dialog to the user. If a user clicks OK in the dialog, the printer selected in the dialog becomes the selected printer for the Snagit capture object.	[in] IParentHandle (long): Handle to windows (hwnd) in 32-bit integer format. If handle is not available, set value to 0. [out] dialogAccepted (Boolean): True if the user clicked OK to select a new printer. False if the user clicked cancel.	If the user clicks OK on the printer selection dialog, any data set by a call to SetData is overwritten. If UseDefault:Printer is set to true, any selection made by the user is ignored.

Properties

Property (type)	Default	Read / Write	Notes
UseDefault:Printer (Boolean)	True	Write	If true, the capture is sent to the system default printer. When set to true, this property overrides any other printer settings.

IPrinterPageLayoutOptions

The **IPrinterPageLayoutOptions** interface is used to specify how to format the output going to the printer. These options are only used when either **sioPrinter** or **stoPrinter** is selected as the output for the capture object.

Properties

Property (type)	Default	Read / Write	Notes
Height (long)	4000	Write	The height, in thousandths of an inch, of the capture as it appears on the printed page.
LayoutPosition (snag-Placement)	spLeftTop	Write	Sets the placement of the capture as it appears on the printed page.
MarginBottom (long)	0	Write	Sets the minimum distance, in thousandths of an inch, placed between the bottom edge of the printed page and the bottom of the capture.
MarginLeft (long)	0	Write	Sets the minimum distance, in thousandths of an inch, placed between the right edge of the printed page and the right side of the capture.
MarginRight (long)	0	Write	Sets the minimum distance, in thousandths of an inch, placed between the right edge of the printed page and the top of the capture.
MarginTop (long)	0	Write	Sets the minimum distance, in thousandths of an inch, placed between the top edge of the printed page and the top of the capture.
Scale (long)	100	Write	Sets the scale of the capture on the printed page as a percentage.
ScalingType (snag-PrintScale)	spsFixedSize	Write	Sets the type of scaling to perform. See snag-PrintScale for the available options.
Width (long)	4000	Write	The width, in thousandths of an inch, of the capture as it appears on the printed page.

IRegionOptions

The **IRegionOptions** interface contains all the settings for a region capture (input set to **siiRegion** or **stiRegion**). These options are only valid when using **siiRegion** or **stiRegion** as the input type.

Properties

Properties (type)	Default	Read / Write	Notes
Height (long)	240	Write	Sets the height for the rectangular region to capture. Must be a positive integer.
SelectionMethod (sna-gRegionSelectionMethod)	srsmlInteractive	Write	Sets the type of region capture to perform. The default allows for the user to click and drag to select a region.
StartX (long)	0	Write	Sets the starting X coordinate in pixels of the rectangular region to capture. Ignored if UseStartPosition is set to false.
StartY (long)	0	Write	Sets the starting Y coordinate in pixels of the rectangular region to capture. Ignored if UseStartPosition is set to false.
UseStartPosition (Boolean)	False	Write	When true, the capture is performed with no user input. The capture region is defined by the Height , Width , StartX , and StartY properties.
Width (long)	320	Write	Sets the width for the rectangular region to capture. Must be a positive integer.

ISelectedArea

The **ISelectedArea** interface exposes the bounding box around the captured area. For a rectangular region, this is exactly the same. For an irregular region like a freehand area, this is the bounding box around that area (left-most point in the area, right-most, etc).

Properties

Property (type)	Default	Read / Write	Notes
StartX (long)	0	Write	The X coordinate of the upper left corner of the bounding box.
StartY	0	Write	The Y coordinate of the upper left corner of the bounding box.

Property (type)	Default	Read / Write	Notes
(long)			
Height (long)	0	Write	Sets the height, in "ems," to use for the font. The system uses the nearest height to the specified value that does not exceed it.
Weight (long)	0	Write	Sets the weight, or thickness, of the font.

ITextAnnotation

The **ITextAnnotation** interface is used to add a caption to a capture.

Properties

Property (type)	Default	Read / Write	Notes
EnableCaption (Boolean)	False	Write	If true, a text caption is added to the capture.
PromptForCaption (Boolean)	False	Write	Prompts the user for text to use in the caption.
CaptionText (string)	"" (empty string)	Write	The text to use in the caption. If PromptForCaption is true, the text in this property is ignored.
IncludeComputerName (Boolean)	False	Write	Adds the name of the computer to the caption.
IncludeUserName (Boolean)	False	Write	Adds the name of the current user to the caption.
IncludeTimeDate (Boolean)	False	Write	Appends the time and date to the caption.
TimeDateDisplayOrder (snagTimeDateOrder)	stdoTimeThenDate	Write	Defines in what order the time and date are displayed.
UserWindowsTimeFormat (Boolean)	True	Write	Use the system's default time format.
UserWindowsDateFormat (Boolean)	False	Write	Use the system's default date format.

Property (type)	Default	Read / Write	Notes
CustomTimeFormat (string)	"" (empty string)	Write	This text represents the format of the time, such as "h:mm:ss tt".
CustomerDateFormat (string)	"" (empty string)	Write	This text represents the format of the date, such as "M/d/yyyy".

ITextFont

The **ITextFont** interface specifies font properties for text output. Fonts also show in the Editor window.

Properties

Property (type)	Default	Read / Write	Notes
Height (long)	12	Write	Sets the height, in "ems," to use for the font. The system uses the nearest height to the specified value that does not exceed it.
Weight (long)	400	Write	Sets the weight, or thickness, of the font. Use a value of 400 for normal text and 700 for bold text. Valid values are 0 - 1000.
Italic (long)	0	Write	If true, the text is written in italics.
Underline (long)	0	Write	If true, the text is underlined.
PitchFamily (long)	1	Write	For more information, see the LOGFONT struct in the Microsoft documentation.
CharacterSet (long)	0	Write	For more information, see the LOGFONT struct in the Microsoft documentation.
FaceName (string)	"Arial"	Write	The font face name such as "Courier", "Times New Roman", or "Sans Serif" to use.

ITWAINOptions

The **ITWAINOptions** interface contains all the settings for a TWAIN capture (input set to **siiTwain**).

Methods

Method	Action	Parameters	Notes
ShowSelectionDialog (Long, IParentHandle, Boolean dialogAccepted)	Displays a TWAIN device selection dialog to the user. If the user clicks OK in the dialog, the TWAIN device selected in the dialog becomes the selected TWAIN device for the Snagit capture object.	[in] IParentHandle (long): Handle to windows (hwnd) in 32-bit integer format. If handle is not available set value to 0. [out] dialogAccepted (Boolean): True if the user clicked OK to select a TWAIN device and false if the user clicked Cancel.	If this dialog is shown to the user and a TWAIN device is selected, it has no affect unless the input of the image capture object is set to siitwain .

Properties

Property (type)	Default	Read / Write	Notes
Source (string)	"" (empty string)	Write	Specifies by name the TWAIN source to use.

IVideoCapture

The **IVideoCapture** interface contains the settings for use when capturing a video.

Snagit version 11.1.0 or later is required.

Methods

Name	Action	Notes
Capture	Invokes the video recording.	This could include selecting the region to record when using the Snagit Recording interface. You can poll the IsCaptureDone property or subscribe to _ICaptureEvents to determine when the recording is finished.
Start	Begins recording video.	This can be called, instead of Capture, to invoke a recording and is intended for clients that implement their

Name	Action	Notes
		own recording interface.
Pause	Pauses a recording.	This is intended for clients that implement their own recording interface.
Resume	Continues a recording.	This is intended for clients that implement their own recording interface.
Stop	Stops a recording.	This is intended for clients that implement their own recording interface.
AudioDevices	Obtains a list of audio recording devices that are available on a system.	Outputs[out]: SAFEARRAY(BSTR) audio device names, SAFEARRAY(LONG) device Ids

Properties

Property (type)	Default	Read / Write	Notes
AudioDevice (long)	Windows default device	Write	Sets the audio device to record with. Returns: The currently selected audio device Id.
AverageFrameRate (float)		Read-only	Gets the overall average frame rate.
CaptureState (snag-CaptureState)	scsIdle	Read-only	Gets the current capture state.
EnablePreviewWindow (Boolean)	FALSE	Write	Sets previewing the video in the editor.
EncoderErrorCode (unsigned int)		Read-only	Gets the internal encoder error code.
ForegroundPreview (Boolean)	Enabled	Write	When enabled, forces the editor window to the foreground after making a recording. This is only valid if the EnablePreviewWindow property has been enabled.
FrameCount (unsigned long)		Read-only	Gets the current total frames recorded.

Property (type)	Default	Read / Write	Notes
HideRecordingUI (Boolean)	FALSE	Write	Enables/disables the Snagit video recording interface. Disable this if you want to show your own recording interface.
IncludeCursor (Boolean)	TRUE	Write	Enables/disables including the mouse cursor in the video recording.
Input (snagVideoInput)	sviCapture	Write	Changes the selection input type.
InputRegionOptions (IRegionOptions)		Read-only	An interface containing all the settings for a Region capture (input set to siiRegion or stiRegion).
InputWindowOptions (IWindowOptions)		Read-only	An interface containing the settings for a Window capture (input set to siiWindow or stiWindow).
IsCaptureDone (Boolean)	FALSE	Read-only	After a call to the Capture method has been made, this property tests to see if the capture has been completed. This property blocks and performs a polling to see when the capture state goes back to scsIdle .
LastCaptureSucceeded (Boolean)	TRUE	Read-only	Returns true if the last capture attempt was successful. Returns false if the last capture attempt was unsuccessful.
LastError (snagError)	serrNone	Read-only	Holds the last error set in the Snagit COM server. If an application subscribes to the OnStateChange event of the _ICaptureEvents interface, this property can be read for the error on a scsCaptureFailed state change. This property is reset to serrNone when a new call to the Capture method is made.
LastRecorderError (snagRecorderError)	srErrNone	Read-only	Returns the last recorder error. <div>You may want to get the specific error code by using the EncoderErrorCode or</div>

Property (type)	Default	Read / Write	Notes
			RecorderErrorCode property before contacting technical support.
MuteMic (Boolean)	FALSE	Write	Enables/disables recording audio from the selected microphone.
MuteSystemAudio (Boolean)	FALSE	Write	Enables/disables recording system audio sounds.
Output (snagVideoOutput)	svoFile	Write	Set this to specify where to output your video recording (file, FTP, or preview in editor).
OutputFTPOptions (IFTPOptions)		Read-only	An interface containing settings for sending the capture out to FTP (output set to sioFTP or stoFTP). At a minimum, server and filename must be set.
OutputVideoFile (IVideoFile)		Read-only	An interface for the configuration of the output file (location and naming).
RecorderErrorCode (int)		Read-only	Gets the internal recorder error code.
RecordingDuration (unsigned long)		Read-only	Returns the total duration of the video recording.
UseMagnifierWindow (Boolean)	TRUE	Read-only	When enabled, a magnifier window shows next to the capture crosshairs for precision when defining capture regions.
VideoFormat (IVideoFormat)	MP4	Read-only	At this time, you do not need to specify the output video file type since we only currently offer MP4.

IVideoFile

The IVideoFile interface contains the settings for the configuration of the output video file. It provides control over the file naming options and output location.

Properties

Property (type)	Default	Read / Write	Notes
AutoFilePrefix (string)	"SNAG-"	Write	When the FileNamingMethod is set to sofnmAuto , this string is the prefix used to automatically name files.
AutoNumPrefixDigits (long)	4	Write	When FileNamingMethod is set to sofnmAuto , this property specifies the number of digits to include in the automatically named output file.
Directory (string)	"" empty string	Write	Sets the directory for the output file. If the FileNamingMethod is not set to sofnmPrompt , the Snagit COM server fails if this property is not set.
Filename (string)	"SNAGIT"	Write	Specifies the output filename to use. This is only used if FileNamingMethod is set to sofnmFixed .
FileNamingMethod (snag-OutputFileNamingMethod)	sofnmPrompt	Write	Method for naming the output file.

IWindowOptions

The **IWindowOptions** interface contains the settings for use when capturing a window. These options are only valid when using **siiWindow** or **stiWindow** as the input type.

Properties

Property (type)	Default	Read / Write	Notes
SelectionMethod (snag-WindowSelectionMethod)	swsmInteractive	Write	Specifies the method used to select the window for capture.
Handle (string)	0 (long)	Write	Specifies the window handle of the window to capture.
XPos (string)	0 (long)	Write	Specifies the X coordinate of a point on the screen. Used in combination with the

Property (type)	Default	Read / Write	Notes
			Y coordinate to capture the window under that point.
YPos (string)	0 (long)	Write	Specifies the Y coordinate of a point on the screen. Used in combination with the X coordinate to capture the window under that point.

Enumerations

The following section describes pre-defined data objects used throughout the Snagit COM server.

- ▶ **snagAutoScrollMethod**
- ▶ **snagAutoScrollStartingPosition**
- ▶ **snagCaptionTextStyle**
- ▶ **snagCaptureState**
- ▶ **snagColorConversionMethod**
- ▶ **snagColorSubMethod**
- ▶ **snagCompassDirection**
- ▶ **snagError**
- ▶ **snagHotspotType**
- ▶ **snagImageColorDepth**
- ▶ **snagImageFileSubType**
- ▶ **snagImageFileType**
- ▶ **snagImageInput**
- ▶ **snagImageOutput**
- ▶ **snagImageScaleBy**
- ▶ **snagImageScaleMethod**
- ▶ **snagNotificationType**
- ▶ **snagOutputFileNamingMethod**
- ▶ **snagPlacement**
- ▶ **snagPrintScale**
- ▶ **snagRecorderError**
- ▶ **snagRecorderState**
- ▶ **snagRegionSelectionMethod**
- ▶ snagTextInput
- ▶ snagTextLayout
- ▶ snagTextOutput
- ▶ **snagTimeDateOrder**
- ▶ **snagTrimMethod**
- ▶ **snagVideoFileType**
- ▶ **snagVideoInput**
- ▶ **snagVideoOutput**
- ▶ **snagWindowSelectionMethod**

snagAutoScrollMethod

An enumeration used to scroll windows or regions automatically.

Name	Value	Description
sasmNone	0	Do not automatically scroll a window or region.

Name	Value	Description
sasmVertical	1	Automatically scroll the window or region down vertically.
sasmHorizontal	2	Automatically scroll the window or region to the right horizontally.
sasmBoth	3	Automatically scroll the window or region both down and to the right.

snagAutoScrollStartingPosition

An enumeration used to set the starting location for automatically scrolling a window.

Name	Value	Description
sasspCurrent	0	Begin the automatic scroll from the current position.
sasspTop	1	Scroll to the top of the window before starting the automatic scrolling capture.
sasspLeft	2	Scroll to the left of the window before starting the automatic scrolling capture.
sasspTopLeft	3	Scroll to the top and left of the window before starting the automatic scrolling capture.

snagCaptionTextStyle

An enumeration used to set the text style in captions placed in images.

Name	Value	Description
sctsNormal	0	Text captions on an image have no special effect.
sctsDropShadow	1	Text captions on an image have a drop shadow.
sctsOutlinedShadow	2	Text captions on an image have an outlined shadow.

snagCaptureState

An enumeration used to set the state of the Snagit COM server during capture.

Name	Value	Description
scsIdle	0	The Snagit COM server is not currently taking a capture.
scsCaptureSucceeded	10	The capture was completed successfully.
scsCaptureFailed	11	The capture failed or was canceled.

Name	Value	Description
scsBusy	12	The capture process has not yet completed (e.g. waiting for user input on a dialog).

snagColorConversionMethod

An enumeration used to change image colors.

Name	Value	Description
sccmNone	0	No color conversion.
sccmMonochrome	1	Change the captured image to monochrome (black and white).
sccmHalftone	2	Change the captured image to dithered monochrome.
sccmGrayscale	3	Change the captured image to grayscale.

snagColorSubMethod

An enumeration used to set how colors are replaced in an image.

Name	Value	Description
scsmNone	0	Leave the same colors in the image.
scsmInvert	1	Invert the color values (255 - x for each of Red, Blue, and Green).
scsmCustom	2	Use the values specified by the user.

snagCompassDirection

An enumeration used to set direction specifications.

Name	Value	Description
scdNorth	0	Up
scdNorthEast	1	Up and right
scdEast	2	Right
scdSouthEast	3	Down and right
scdSouth	4	Down
scdSouthWest	5	Down and left

Name	Value	Description
scdWest	6	Left
scdNorthwest	7	Up and left

snagError

An enumeration used to set the type of error reported by the Snagit COM server.

Name	Value	Description
serrUnknown	-1	An unknown error occurred
serrNone	0	No error
serrSnagitExpired	1	Expired evaluation version of Snagit
serrInvalidInput	2	An invalid input was specified for the capture object
serrInvalidOutput	3	An invalid output was specified for the capture object
serrEngineBusy	4	The capture engine is currently busy
serrInvalidScrollDelay	5	The scroll delay specified for the automatic scrolling parameter was invalid
serrInvalidDelay	6	Delay capture has an invalid delay time
serrInvalidColorEffectValue	7	One of the values set for a color effect is invalid
serrInvalidFileProgressiveValue	8	The progressive value setting in ImageFile is not valid
serrInvalidFileQualityValue	9	The file quality setting in ImageFile is not valid
serrInvalidFileDirectory	10	A valid directory is not specified for ImageFile output
serrInvalidColorConversionValue	11	An invalid color conversion value was specified in the ImageColorConversion settings
serrInvalidImageResolution	12	An invalid image resolution value was specified in the ImageResolution settings

snagHotspotType

An enumeration used to set the types of controls to capture and create as hotspots.

Name	Value	Description
shtUnknown	-1	The hotspot type is unknown
shtNone	0	Do not capture hotspots
shtLinksOnly	1	Turn links found on webpages into hotspots in the image
shtLinksAndControls	2	Turn links, buttons, tabs, and other controls into hotspots in the image

snagImageColorDepth

An enumeration used to set the number of bits used to represent a color in an image.

Name	Value	Description
sicdAuto	0	Automatically choose the color depth for the image.
sicd1Bit	1	Use 1 bit to specify the color (monochrome)
sicd2Bit	2	Use 2 bit color
sicd3Bit	3	Use 3 bit color
sicd4Bit	4	Use 4 bit color
sicd5Bit	5	Use 5 bit color
sicd6Bit	6	Use 6 bis color
sicd7Bit	7	Use 7 bit color
sicd8Bit	8	Use 8 bit color
sicd16Bit	16	Use 16 bit color
sicd24Bit	24	Use 24 bit color (truecolor)
sicd32bit	32	Use 32 bit color (truecolor plus transparency information)

snagImageFileSubType

An enumeration used to set the subtypes for image file formats.

Name	Value	Description
sifstUnknown	-1	Unknown format
sifstBMP_Uncompressed	0x0000001	Uncompressed Windows bitmap

Name	Value	Description
sifstBMP_RLE	0x0000002	Windows bitmap with Run-Length Encoding
sifstGIF_NonInterlaced	0x0000004	Non-interlaced GIF
sifstGIF_Interlaced	0x0000008	Interlaced GIF
sifstJFIF_444	0x0000010	JPEG non-progressive 4:4:4
sifstJFIF_422	0x0000020	JPEG non-progressive 4:2:2
sifstJFIF_411	0x0000040	JPEG non-progressive 4:1:1
sifstJFIF_444_Progressive	0x0000080	JPEG progressive 4:4:4
sifstJFIF_422_Progressive	0x0000100	JPEG progressive 4:2:2
sifstJFIF_411_Progressive	0x0000200	JPEG progressive 4:1:1
sifstJFIF_Gray	0x0000400	JPEG non-progressive grayscale
sifstJFIF_Gray_Progressive	0x0000800	JPEG progressive grayscale
sifstCCITT	0x0001000	TIFF subtype for fax
sifstCCITT_Group3_1Dimension	0x0002000	TIFF subtype for fax
sifstCCITT_Group3_2Dimension	0x0004000	TIFF subtype for fax
sifstCCITT_Group4	0x0008000	TIFF subtype for fax
sifstTIF_Uncompressed	0x0010000	Uncompressed TIFF
sifstTIF_PackBits	0x0020000	PackBits compressed TIFF
sifstTIF_LZW	0x0040000	LZW compressed TIFF
sifstJTIF_Gray	0x0080000	JPEG compressed grayscale TIFF
sifstTIF_CMYK	0x0100000	Uncompressed TIFF using CMYK colorspace
sifstTIF_YCC	0x0200000	Uncompressed TIFF using YCC colorspace
sifstTIF_PACK_CMYK	0x0400000	PackBits compressed TIFF using CMYK colorspace
sifstTIF_PACK_YCC	0x0800000	PackBits compressed TIFF using YCC colorspace
sifstTIF_LZW_CMYK	0x1000000	LZW compressed TIFF using

Name	Value	Description
		CMYK colorspace
sifstTIF_LZW_YCC	0x2000000	LZW compressed TIFF using YCC colorspace
sifstJTIF_444	0x4000000	JPEG compressed TIFF 4:4:4
sifstJTIF_422	0x8000000	JPEG compressed TIFF 4:2:2
sifstJTIF_411	0x10000000	JPEG compressed TIFF 4:1:1

snagImageFileType

An enumeration used to set the format of an image file.

Formats with values from 7 to 27 are only available for Snagit version 8.1 and higher.

Name	Value	Description
siftUnknown	-1	Unknown format
siftBMP	0	Windows bitmap
siftTIFF	2	Tagged Image File Format
siftJPEG	3	JPEG
siftGIF	4	CompuServe GIF
siftPNG	5	Portable Network Graphic
siftTGA	6	Truevision Targa
siftRAS	7	SUN Raster
siftWMF	9	Windows Metafile
siftEPS	11	Encapsulated Postscript
siftOS2	17	OS/2 Bitmap
siftWFX	18	WinFax
siftEMF	19	Windows Enhanced Metafile
siftWPG	20	WordPerfect
siftPSD	21	Adobe PhotoShop 3.0

Name	Value	Description
siftICO	22	Windows icon
siftCUR	23	Windows cursor
siftPDF	24	Adobe PDF
siftSNAG	25	Snagit Capture File
siftSWF	26	Adobe Shockwave Flash
siftMHT	27	Web Page with Image (MHTML)

snagImageInput

An enumeration used to set the type of capture.

Name	Value	Description
siiDesktop	0	Capture the full screen
siiWindow	1	Capture one window
siiRegion	4	Capture a region of the screen
siiGraphicFile	6	Capture an existing graphic file
siiClipboard	7	Capture the contents of the Clipboard
siiMenu	9	Capture a menu
siiObject	10	Capture an object (user interactive)
siiFreehand	12	Capture a user drawn freehand region of the screen
siiCustomScroll	18	User draws a region and then clicks a scroll button. Capture continues until the window has scrolled to the bottom.
siiTWAIN	19	Capture from a TWAIN source (usually a scanner)
siiExtendedWindow	23	REsize a window before capture. The size of the window (potentially larger than the screen resolution) is specified in advance or by the user.
siiCapture	25	Capture using the All-in-One Capture® input, allowing window, region or scrolling window capture.

snagImageOutput

An enumeration used to set the output of a captured image.

Name	Value	Description
sioNone	0	No output is set
sioPrinter	1	Send the captured image directly to the printer
sioFile	2	Save the image to a file. The filename can be specified, automatically generated, or prompted for.
sioClipboard	4	Place the captured image in the system Clipboard
sioMail	8	Send the image as an attachment in an email. This start the system default email client. Uses settings in IMailOptions .
sioFTP	32	Upload an image file to an FTP server. See IFTPOptions

snagImageScaleBy

An enumeration used to set the scaling dimensions of the image.

Name	Value	Description
sisbFactor	0	Scale the image by multiplicative factor
sisbWidthAndHeight	1	Scale to match a given width and height
sisbWidth	2	Scale width to match a specified value
sisbHeight	3	Scale height to match a specified value

snagImageScaleMethod

An enumeration used to change the size of a captured image.

Name	Value	Description
sismCustom	0	Use custom scaling options defined in <code>ImageScale</code>
sismPercentage	1	Scale by percentage
sismNone	2	Do not scale image

snagNotificationType

An enumeration used to set the types of messages Snagit displays. These are not related to event handling.

Name	Value	Description
sntNone	0	No notifications are displayed

Name	Value	Description
sntInformation	1	Informational dialogs are displayed
sntErrors	2	Error messages are displayed
sntAll	3	Both error and informational dialogs are displayed

snagOutputFileNamingMethod

An enumeration used to determine how files are named during file output.

Name	Value	Description
sofnmPrompt	0	The user is prompted for the name and location to save the file. Use with sioFile and stoFile .
sofnmFixed	1	The file is saved with a fixed file name specified by the program. Specified in lImageFile or lImageFile2 .
sofnmAuto	2	The file is saved with an automatically generated name.

snagPlacement

An enumeration used to set the placement of objects.

Name	Value	Description
spUnknown	-1	Placement unknown
spLeftTop	0	Place in upper left
spRightTop	1	Place in upper right
spLeftBottom	2	Place in lower left
spRightBottom	3	Place in lower right
spCenterMiddle	4	Place in the center
spCenterTop	5	Place in the center of the top
spLeftMiddle	6	Place in the middle of the left
spRightMiddle	7	Place in the middle of the right
spCenterBottom	8	Place in the center of the bottom
spOutsideTop	9	Place on the outside top of the capture

Name	Value	Description
spOutsideLeft	10	Place on the outside left of the capture
spOutsideBottom	11	Place on the outside bottom of the capture
spOutsideRight	12	Place on the outside right of the capture

snagPrintScale

An enumeration used to set how an image is fitted on a page for printer output.

Name	Value	Description
spsSinglePage	0	The image, regardless of size, is scaled to fit on one page.
spsPercentScale	1	A scaling percentage is applied to decrease or increase the image's size on the printed page. An image printed at 100 percent is the same as one printed with the spsProportionalToScreen setting.
spsProportionalToScreen	2	The relationship between the width of the area captured and the width of the screen is used to calculate the width of the printed image in relation to the width of the printed page.
spsFixedSize	3	The width and height are fixed, scaling or distorting the image if necessary.
spsSinglePageMaximize	4	The image is made as large as possible while still fitting on one page. This setting preserves the aspect ratio of the original image.
spsAutoScale	5	The width of the image is scaled to the width of the page. The length is scaled in proportion and can be more than one page.

snagRecorderError

An enumeration used to set the type of recording error reported by the Snagit COM server.

Name	Value	Description
srErrNone	0	No errors
srErrInitRecorderFailed	1	Error occurred while initializing the video recorder
srErrInitRecorderFailed	2	Error occurred while initializing the video encoder
srErrRecorderThrownCode	3	There was a recorder error.

Name	Value	Description
		The specific error code can be retrieved.
srErrEncoderThrownCode	4	There was an encoder error. The specific error code can be retrieved.
srErrStarting	5	There was an error trying to start the recording.
srErrPausing	6	There was an error trying to pause the recording.
srErrResuming	7	There was an error when trying to resume recording.
srErrStopping	8	There was an error stopping the recording.
srErrDiskSpaceLow	9	The disk drive that contains the user's \AppData\Local\Temp folder is running out of free space.
srErrInvalidRecordingRect	10	The selected region to record is outside of the Snagit recording limits minimum 64 x 64 pixels, maximum 1920 x 1080 pixels.
srErrSystemAudioNotAvailable	11	No device was found in which to record your system audio.
srErrUnknown	99	Unknown error

snagRecorderState

An enumeration used to set the state of the Snagit COM server recording.

Name	Value	Description
srStateInitialized	-1	This is the initial recorder state.
srStateCounting	0	This state is only used when the recording UI is enabled and indicates that it is doing the count down.
srStateRecording	1	The recorder is now capturing video.
srStatePausing	2	The recorder is pausing.
srStateStopping	3	The recorder is stopping.

Name	Value	Description
srReselecting	4	This state is only used when the recording interface is enabled and indicates that the user is reselecting a recording area.

snagRegionSelectionMethod

An enumeration used to specify what method to use when capturing a region.

Name	Value	Description
srsmlInteractive	0	Interactively click and drag a region to be captured.
srsmlFixed	1	Use values provided to capture a region of fixed size. This may still be interactive if a starting X and Y position is not given.

snagTimeDateOrder

An enumeration used to set the order of time and date for timestamps.

Name	Value	Description
stdoTimeThenDate	0	Show time and then date
stdoTimeOnly	1	Show only the time
stdoDateThenTime	2	Show the date and then the time
stdoDateOnly	3	Show only the date

snagTrimMethod

An enumeration used to cut the outside borders of captured images.

Name	Value	Description
stmNone	0	No trimming is performed
stmManual	1	The edge of the image is trimmed by the number of pixels specified
stmAuto	2	Automatically trim blank areas from the edges of captured images. A blank area on an image is one that has no change in color.

snagVideoFileType

An enumeration used to set the format of the video file.

Name	Value	Description
svftUnknown	-1	Unknown file format
svftMP4	0	MPEG-4 file (default)

snagVideoInput

An enumeration used to set the input selection type.

Name	Value	Description
sviWindow	1	Record a window
sviRegion	4	Record a region of the screen
sviCapture	25	Record using the All-in-One input, allowing for selecting a region or a window

snagVideoOutput

An enumeration used to set the output of the recording.

Name	Value	Description
svoNone	0	Preview the recording in Snagit Editor
svoFile	2	Save the video to a file. The filename can be specified, automatically generated, or prompted for
svoFTP	32	Upload a recording to a FTP server

snagWindowSelectionMethod

An enumeration used to specify how to make a window selection.

Name	Value	Description
swsmInteractive	0	The user selects a window to capture
swsmActive	1	Capture the currently active window
swsmHandle	2	Capture the window with the given window handle (as a long value)
swsmPoint	3	Capture the window under the point specified with X and Y coordinates

Events

The **_ICaptureEvents** interface is an event interface used for callbacks. A client program may choose to subscribe to events from the Snagit COM Object.

Methods

Name	Action	Parameters	DisplID
OnError	Occurs when there is an error in the capture object.	[in] Error (snagError): The code for the error that occurred.	1
OnStateChange	Occurs when there is a state change in the capture object.	[in] State (snagCaptureState): The code for the state change that occurred.	2
OnFileWritten	Occurs when a file is written to notify the client program of the filename.	[in] Filename (string): The filename that was written.	3

_IRecorderEvents Methods

The **_IRecorderEvents** is an event interface used for callbacks for clients that implement their own recording interface. A client program may choose to subscribe to events from the Snagit COM Object.

Name	Action	Parameters	DispID
OnAudioVolumeLevel	The recorder sends volume level events as a percentage (0 – 100).	(int) Percent	1
OnRecorderError	Occurs when there is an error by Snagit Recorder. <div> This is not the same as the OnError from the _ICaptureEvents interface </div>	(sna-gRecorderError) Error	2
OnRecorderStateChange	Occurs when the Snagit Recorder changes recording states.	(sna-gRecorderState) newState	3
OnMuteDeviceChanged	Occurs when using the Snagit Recording interface and the user clicks the mute device control.	(VARIANT_BOOL) bMuted	4
OnMuteSystemAudioChanged	Occurs when using the Snagit Recording interface and the user just clicks the Mute System Audio option.	(VARIANT_BOOL) bMuted	5
OnSelectedRecordingRegion	Occurs when using the Snagit selection interface and the user has finished selecting the region to record.	(long) xOffset, (long) yOffset, (long) rectWidth, (long) rectHeight	6

Data Types

Boolean

True (-1) or False (0)

Many languages have defines for true and false values; these may or may not be translated to the correct `VARIANT_BOOL` values. For example, C++/ATL programs should use the `VARIANT_TRUE` and `VARIANT_FALSE`, whereas Visual Basic, Visual Basic .NET, Visual Basic Script, and C# correctly translate the default `true` and `false` values.

Long

32-bit signed integer

String

Variable length string

► C++/ATL: `BSTR` or `CCoBSTR`

Interface

All interfaces are derived from `IDispatch` for use in scripting languages such as Visual Basic Script

Colors

Colors are represented as long values where the format is :

`0x00bbgrr`

Languages such as MFC and Visual Basic define the macro `RGB(r, g, b)` that correctly creates this value from the three component values.

Code Samples

Example code for the Snagit COM server is available in the following languages:

- ▶ **C++/ATL**
- ▶ **C#**
- ▶ **Visual Basic .NET**
- ▶ **Visual Basic Script**
- ▶ **Visual Basic**

C++/ATL

Code samples for the C++/ATL language.

Import the table implementation file (Snagit.tlb)

```
#import "Path\To\Snagit.tlb" rename_namespace("Snagit")
```

Declare an object

- ▶ Snagit Version 6.2 and later

```
Snagit::IImageCapturePtr pImageCapture; // v6.2 and later
```

- ▶ Snagit Version 8.1 and later

```
Snagit::IImageCapture2Ptr pImageCapture; // v8.1 and later
```

Create an object

```
pImageCapture.CreateInstance( __uuidof( Snagit::ImageCapture ) );
```

Handle objects

To handle objects takes several steps. Capturing error events is illustrated here.

1. At the top of your class declaration file create an external reference to an `_ATL_FUNC_INFO` object.

```
extern _ATL_FUNC_INFO SnagitErrorInfo;
```

2. Next have your class inherit from the `IDispatchSimpleImpl` templated class.

```
class CMyClass : IDispEventSimpleImpl<1, CMyClass, &__uuidof
(Snagit::_ICaptureEvents)>
```

3. Next create a typedef inside your class declaration to talk about the events more easily.

```
typedef IDispEventSimpleImpl<1, CMyClass, &__uuidof(Snagit::_
ICaptureEvents)> SnagitErrorEvents;
```

4. Now create a sink map inside your class declaration to setup the message handling

```
BEGIN_SINK_MAP(CMyClass)

    SINK_ENTRY_INFO(1, __uuidof( Snagit::_ICaptureEvents
    ), 0x01, OnSnagitError, SnagitErrorInfo )

END_SINK_MAP()
```

5. Declare the message handler function inside your class declaration

```
void __stdcall OnSnagitError( Snagit::snagError nErrorCode );
```

6. Now in your class implementation file, define the SnagitErrorInfo _ATL_FUNC_INFO object

```
_ATL_FUNC_INFO SnagitErrorInfo = { CC_STDCALL, VT_EMPTY, 1, {
VT_I4 } };
```

7. Before you start getting events, you must advise the object that you are listening for events somewhere in the implementation file

```
SnagitErrorEvents::DispEventAdvise( pImageCapture );
```

8. Lastly, implement the handler function

```
void __stdcall CMyClass::OnSnagitError( Snagit::snagError nEr-
rorCode )

{

    /* implementation */

}
```

C#

Code samples for the C# language.

Declare an object

- ▶ Snagit Version 6.2 and later

```
private SNAGITLib.ImageCapture ImageCap; // v6.2 and later
```

- ▶ Snagit Version 8.1 and later

```
private SNAGITLib.IImageCapture2 ImageCap; // v8.1 and later
```

Create an object

```
ImageCap = new SNAGITLib.ImageCaptureClass();
```

Handle callbacks

To handle callbacks, create a function that handles the callback and attach it to the object using the correct delegate.

```
ImageCap.OnError += new SNAGITLib._ICaptureEvents_OnEr-  
rorEventHandler( this.OnError );
```

Visual Basic .NET

Code sample for the Visual Basic .NET language.

Declare an object

- ▶ Snagit Version 6.2 and later

```
Public ImageCapture1 As SNAGITLib.ImageCapture ' v6.2 and later
```

- ▶ Snagit Version 8.1 and later

```
Public ImageCapture1 As SNAGITLib.IImageCapture2 ' v8.1 and later
```

Declare an object able to receive events

```
Public WithEvents ImageCapture1 As SNAGITLib.ImageCapture
```

Create an object

```
ImageCapture1 = New SNAGITLib.ImageCaptureClass()
```

If an object is created with the ability to receive events

```
'This function handles the OnStateChange event from the Image-  
Capture object  
  
Private Sub CapState(ByVal capState As SNAGITLib.snagCaptureState)  
Handles ImageCapture1.OnStateChange  
  
...  
  
...  
  
End Sub
```

Visual Basic Script

Code sample for the Visual Basic Script language.

Create an object

```
'Create and image capture object  
  
set ImageCap = CreateObject("SNAGIT.ImageCapture")
```

If the script is allowed to exit before the capture has completed, the capture object will go out of scope and will exit. To keep the script running while the capture finishes a sleeping loop can be used.

```
Do Until ImageCap.IsCaptureDone  
  
    WScript.Sleep 10  
  
Loop
```

Visual Basic

Code sample for the Visual Basic language.

Declare an object

- Snagit Version 6.2 and later

```
Dim ImageCapture As SNAGITLib.ImageCapture ' v6.2 and later
```

- Snagit Version 8.1 and later

```
Dim ImageCapture As SNAGITLib.IImageCapture2 ' v8.1 and later
```

Declare an object able to receive events

```
Dim WithEvents ImageCapture As SNAGITLib.ImageCapture
```

Create an object

```
Set ImageCapture = CreateObject("Snagit.ImageCapture")
```

If an object is created with the ability to receive events

```
' This function handles the OnStateChange event fired by the Image-  
Capture interface  
  
' Event handling is done simply by putting the event after an _  
after the object that  
  
' fires the event. That is, Object_Event  
  
Private Sub ImageCapture_OnStateChange(ByVal capState As SNA-  
GITLib.snagCaptureState)
```